

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113660 A1

(51) International Patent Classification⁷: E06B 7/03,
F24F 13/18

(21) International Application Number:
PCT/CA2004/000944

(22) International Filing Date: 25 June 2004 (25.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,433,443 25 June 2003 (25.06.2003) CA

(71) Applicant and

(72) Inventor: CHATO, John, D. [CA/CA]; 4266 Grange
st., Suite 1907, Burnaby, British Columbia V5J 1P2 (CA).

(74) Agent: RIEDER, Thomas, T.; 301 Petheram Pl., New-
market, Ontario L3X 1J8 (CA).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: INSULATING BAFFLE FOR WINDOW SPACE



(57) Abstract: A baffle is provided for insertion between the edge of
a window and the edge of a recess along which the window can re-
ciprocate. The baffle includes at least two block members each with a
section resembling a "S" that defines top and bottom surfaces and fur-
ther defines two internal oppositely-opening slots, and two elongate
frame members each having a portion adjacent one of the surfaces and
a further portion received in one of the slots.

WO 2004/113660 A1